











| OBIEKT : <b>Budynek mieszkalny 5 w Czeladzi</b> |        |      |                                   | <b>WYKAZ STALI 6</b>    |                  |                    |      |        |    |        |       |    |    |
|---|--------|------|-----------------------------------|-------------------------|------------------|--------------------|------|--------|----|--------|-------|----|----|
| ELEMENT : <b>B2-ściany garażu budynek 5</b>     |        |      |                                   | NR RYSUNKU : K6 STRONA  |                  |                    |      |        |    |        |       |    |    |
| WYKONAŁ:  |        |      |                                   |                         |                  |                    |      |        |    |        |       |    |    |
| Nr  | Stal   | φ    | KSZTAŁT<br>[ mm ]                 | DŁUG.<br>PRETA<br>[ m ] | ILOSC<br>[ szt ] | DŁUGOSC OGOLNA [m] |      |        |    |        |       |    |    |
|   |        |      |                                   |                         |                  | A-0                |      | A-IIIN |    |        |       |    |    |
|   |        |      |                                   |                         |                  | 6                  | 8    | 8      | 10 | 12     | 16    | 20 | 25 |
| 1   | A-IIIN | 12   | 3470                              | 3,47                    | 830              |                    |      |        |    | 2880,1 |       |    |    |
|   |        |      | pręty poziome przycięć na budowie |                         |                  |                    |      |        |    |        |       |    |    |
| 3   | A-0    | 6    | 50 210 150                        | 0,31                    | 850              | 263,5              |      |        |    |        |       |    |    |
| 4   | A-IIIN | 12   | 4200                              | 4,2                     | 400              |                    |      |        |    | 1680,0 |       |    |    |
| 5   | A-IIIN | 16   | 3470                              | 3,47                    | 120              |                    |      |        |    |        | 416,4 |    |    |
| 6   | A-IIIN | 16   | 4400                              | 4,4                     | 92               |                    |      |        |    |        | 404,8 |    |    |
| 7   | A-0    | 6    | 50 140 150                        | 0,24                    | 800              | 192,0              |      |        |    |        |       |    |    |
| 8   | A-0    | 6    | 50 340 150                        | 0,44                    | 56               | 24,6               |      |        |    |        |       |    |    |
|   |        |      | łączniki w narożach               |                         |                  |                    |      |        |    |        |       |    |    |
| 11  | A-IIIN | 8    | 210 500                           | 1,21                    | 180              |                    |      | 217,8  |    |        |       |    |    |
| 12  | A-IIIN | 8    | 140 500                           | 1,14                    | 294              |                    |      | 335,2  |    |        |       |    |    |
|   |        |      | łączniki przyotworowe             |                         |                  |                    |      |        |    |        |       |    |    |
| 16  | A-IIIN | 8    | 140 250                           | 0,64                    | 112              |                    |      | 71,7   |    |        |       |    |    |
|   |        |      | strzemiona filarów ścian          |                         |                  |                    |      |        |    |        |       |    |    |
| 22  | A-0    | 8 D1 | 320 550 50,50 320                 | 1,84                    | 45               |                    | 82,8 |        |    |        |       |    |    |
| 23  | A-0    | 8 D2 | 320 230 50,50 320                 | 1,2                     | 45               |                    | 54,0 |        |    |        |       |    |    |
| 24  | A-0    | 8 B  | 140 440 50,50 140                 | 1,26                    | 20               |                    | 25,2 |        |    |        |       |    |    |
| 25  | A-0    | 8 A  | 140 360 50,50 140                 | 1,1                     | 10               |                    | 11,0 |        |    |        |       |    |    |
| 26  | A-0    | 8 E  | 140 820 50,50 140                 | 2,02                    | 20               |                    | 40,4 |        |    |        |       |    |    |
| 29  | A-0    | 8 B1 | 140 240 50,50 140                 | 0,86                    | 10               |                    | 8,6  |        |    |        |       |    |    |
|   |        |      |                                   |                         |                  |                    |      |        |    |        |       |    |    |

| OBIEKT : <b>Budynek mieszkalny 5 w Czeladzi</b> |        |    |   | <b>WYKAZ STALI 6</b>    |                  |                    |       |        |    |      |    |       |    |
|---|--------|----|---|-------------------------|------------------|--------------------|-------|--------|----|------|----|-------|----|
| ELEMENT : <b>B2-ściany garażu budynek 5</b>     |        |    |   | NR RYSUNKU : K6 STRONA  |                  |                    |       |        |    |      |    |       |    |
| WYKONAŁ:  |        |    |   |                         |                  |                    |       |        |    |      |    |       |    |
| Nr  | Stal   | φ  | KSZTAŁT<br>[ mm ]   | DŁUG.<br>PRETA<br>[ m ] | ILOSC<br>[ szt ] | DŁUGOSC OGOLNA [m] |       |        |    |      |    |       |    |
|   |        |    |   |                         |                  | A-0                |       | A-IIIN |    |      |    |       |    |
|   |        |    |   |                         |                  | 6                  | 8     | 8      | 10 | 12   | 16 | 20    | 25 |
|   |        |    | nadpr.Nd1 szt.4, Nd2 szt.4,   |                         |                  |                    |       |        |    |      |    |       |    |
| 30  | A-IIIN | 12 |    | 2,6                     | 16               |                    |       |        |    | 41,6 |    |       |    |
| 31  | A-0    | 8  |    | 2,94                    | 56               |                    | 164,6 |        |    |      |    |       |    |
|   |        |    | nadpr.Nd3 szt.1   |                         |                  |                    |       |        |    |      |    |       |    |
| 30  | A-IIIN | 12 |    | 2,6                     | 2                |                    |       |        |    | 5,2  |    |       |    |
| 33  | A-0    | 8  |    | 2,62                    | 7                |                    | 18,3  |        |    |      |    |       |    |
|   |        |    | <b>Słup S1 szt.4</b>  |                         |                  |                    |       |        |    |      |    |       |    |
| 50  | A-IIIN | 20 |    | 3,47                    | 32               |                    |       |        |    |      |    | 111,0 |    |
| 51  | A-0    | 6  |    | 1,46                    | 52               | 75,9               |       |        |    |      |    |       |    |
|   |        |    | <b>Słup S2 szt.2</b>  |                         |                  |                    |       |        |    |      |    |       |    |
| 50  | A-IIIN | 20 |    | 3,47                    | 16               |                    |       |        |    |      |    | 55,5  |    |
| 52  | A-0    | 6  |    | 1,36                    | 52               | 70,7               |       |        |    |      |    |       |    |
|   |        |    | <b>Słup S3 szt.2</b>  |                         |                  |                    |       |        |    |      |    |       |    |
| 50  | A-IIIN | 20 |    | 3,47                    | 16               |                    |       |        |    |      |    | 55,5  |    |
| 53  | A-0    | 6  |  | 1,84                    | 52               | 95,7               |       |        |    |      |    |       |    |
|   |        |    |   |                         |                  |                    |       |        |    |      |    |       |    |

|    |       |       |       |       |       |       |       |       |
|----|-------|-------|-------|-------|-------|-------|-------|-------|
| mb | 722   | 405   | 625   | 0     | 4607  | 821   | 222   | 0     |
| kg | 0,222 | 0,394 | 0,394 | 0,616 | 0,887 | 1,578 | 2,465 | 3,850 |
| kg | 160   | 160   | 246   | 0     | 4088  | 1295  | 547   | 0     |
| kg | 320   |       | 6177  |       |       |       |       |       |
| kg | 6497  |       |       |       |       |       |       |       |

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH ( metoda A wg PN-EN ISO 3766:2005)