












| OBIEKT : Budynek mieszkalny E w Rudzie Śląskiej | | | | WYKAZ STALI | | | | | | | | | |
|--|---------|----|---|--------------------------------------|------------------|--------------------|---|-------|-------|---------|-------|----|---|
| ELEMENT : Ściany oporowe | | | | NR RYSUNKU : K36 STRONA 1 z 1 | | | | | | | | | |
| WYKONAŁ: | | | | | | | | | | | | | |
| Nr | Stal | φ | KSZTAŁT (mm) | DŁUG. PRĘTA [m] | ILOSC [szt] | DŁUGOSC OGOLNA [m] | | | | | | | |
| | | | | | | A-0 | | | | A-IIIIN | | | |
| | | | | | | 6 | 8 | 8 | 10 | 12 | 16 | 20 | 6 |
| 1 | A-IIIIN | 10 | 420  | 2,63 | 66 | | | | 173,6 | | | | |
| 2 | A-IIIIN | 10 |  | 2,39 | 66 | | | | 157,7 | | | | |
| | | | | | | | | | | | | | |
| 4 mb | A-IIIIN | 8 |  | 660 | 1 | | | 660,0 | | | | | |
| 5 mb | A-IIIIN | 16 |  | 140 | 1 | | | | | | 140,0 | | |
| 6 | A-IIIIN | 10 |  | 3,435 | 84 | | | | 288,5 | | | | |
| 7 | A-IIIIN | 10 | 190  | 0,79 | 76 | | | | 60,0 | | | | |
| 8 | A-0 | 6 | 50  | 0,29 | 200 | 58,0 | | | | | | | |
| 10 | A-IIIIN | 10 | 420  | 2,03 | 50 | | | | 101,5 | | | | |
| 11 | A-IIIIN | 10 |  | 1,19 | 50 | | | | 59,5 | | | | |
| 14 | A-IIIIN | 10 | 190  | 2,69 | 146 | | | | 392,7 | | | | |
| 15 | A-IIIIN | 10 |  | 1,67 | 68 | | | | 113,6 | | | | |
| | | | | | | | | | | | | | |

| | | | | | | | | |
|-----------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| mb kg kg kg kg | 58 | 0 | 660 | 1347 | 0 | 140 | 0 | 0 |
| | 0,222 | 0,394 | 0,394 | 0,616 | 0,887 | 1,578 | 2,465 | 0,222 |
| | 13 | 0 | 260 | 830 | 0 | 221 | 0 | 0 |
| | 13 | | 1311 | | | | | |
| 1324 | | | | | | | | |

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)