

OBIEKT : Budynek mieszkalny w Będzinie				WYKAZ STALI 2									
ELEMENT : B - Płyta fundamentowa - segment 1				NR RYSUNKU : K2-K4									
WYKONAŁ:				DATA:									
Nr	Stal	ϕ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St05		A-IIIIN RB500W					
						6	8	8	10	12	16	20	25
wieńce													
1	A-IIIIN	20		12	70							840,0	
2	A-IIIIN	20		6,5	32							208,0	
3	A-IIIIN	20		8	8							64,0	
4	A-IIIIN	20		10,8	16							172,8	
8 mb	A-IIIIN	12		240	1					240,0			
9	A-0	6		1,52	110	167,2							
9A	A-0	6		1,82	16	29,1							
10	A-0	6		1,88	260	488,8							
11	A-0	6		1,54	30	46,2							
12	A-0	6		1,44	216	311,0							
13	A-0	6		1,8	216	388,8							
14	A-0	6		1,36	60	81,6							
			zbrojenie dolne										
15 45°	A-IIIIN	25		4,96	111							550,6	
16	A-IIIIN	16		12	88						1056,0		
17	A-IIIIN	16		4,6	76						349,6		
18	A-IIIIN	16		7,6	218						1656,8		
19	A-IIIIN	16		9,3	130						1209,0		
19A	A-IIIIN	16		10	30						300,0		
20	A-IIIIN	16		6,8	55						374,0		
21	A-IIIIN	16		5,8	12						69,6		
22	A-IIIIN	16		2,5	10						25,0		
23	A-IIIIN	16		8,5	160						1360,0		
24	A-IIIIN	16		3	54						162,0		
25	A-IIIIN	16		3,6	166						597,6		
26	A-IIIIN	10		2,49	650				1618,5				
26A	A-IIIIN	10		2,34	8				18,7				
			zbrojenie górne										
18	A-IIIIN	16		7,6	150						1140,0		
30	A-IIIIN	16		8,6	146						1255,6		

OBIEKT : Budynek mieszkalny w Będzinie				WYKAZ STALI 2									
ELEMENT : B - Płyta fundamentowa - segment 1				NR RYSUNKU : K2-K4						STRONA 2 z 2			
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOŚĆ [szt]	DŁUGOŚĆ OGÓLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	12	16	20	25
31	A-IIIIN	16		8,3	75						622,5		
32	A-IIIIN	16		6,6	160						1056,0		
33	A-IIIIN	16		7	94						658,0		
34	A-IIIIN	16		4,3	85						365,5		
21	A-IIIIN	16		5,8	67						388,6		
21A	A-IIIIN	16		6,6	30						198,0		
35	A-IIIIN	16		6,3	70						441,0		
36	A-IIIIN	16		5,5	160						880,0		
37	A-IIIIN	16		7,3	40						292,0		
			łączniki do ścian i słupów oraz zbrojenie dodatkowe										
40	A-IIIIN	12		2,81	360					1011,6			
41	A-IIIIN	12		2,76	310					855,6			
42	A-IIIIN	12		2,71	38					103,0			
50	A-IIIIN	12		3,79	24					91,0			
51	A-IIIIN	12		4,73	18					85,1			
52	A-IIIIN	12		2,39	24					57,4			
53	A-IIIIN	12		3,39	18					61,0			
54	A-IIIIN	12		2,8	44					123,2			
55	A-IIIIN	12		2,34	40					93,6			
55A	A-IIIIN	8		2,82	3			8,5					
56	A-IIIIN	12		1	22					22,0			
60	A-IIIIN	20		2,4	82							196,8	
61	A-IIIIN	20		2,4	24							57,6	
62	A-IIIIN	16		6,3	2						12,6		
80 mb	A-IIIIN	12		500	1					500,0			
100	A-IIIIN	10		1,67	1350				2254,5				
poz 100- 3szt/m2				mb		1513	0	8	3892	3243	14469	1539	551
				kg		0,222	0,394	0,394	0,616	0,887	1,578	2,465	3,850
				kg		336	0	3	2398	2878	22826	3794	2120
				kg		336		34019					
				kg		34355							

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)