












OBIEKT : Budynek mieszkalny w Będzinie				WYKAZ STALI 2									
ELEMENT : B - Płyta fundamentowa - segment 2				NR RYSUNKU : K2-K4 STRONA 1 z 2									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
				6	8	8	10	12	16	20	25		
wieńce													
1	A-IIIIN	20		12	70						840,0		
2	A-IIIIN	20		6,5	32						208,0		
3	A-IIIIN	20		8	8						64,0		
4	A-IIIIN	20		10,8	16						172,8		
8 mb	A-IIIIN	12		220	1				220,0				
9	A-0	6		1,52	110	167,2							
9A	A-0	6		1,82	0	0,0							
10	A-0	6		1,88	260	488,8							
11	A-0	6		1,54	30	46,2							
12	A-0	6		1,44	216	311,0							
13	A-0	6		1,8	216	388,8							
14	A-0	6		1,36	60	81,6							
zbrojenie dolne													
15 45°	A-IIIIN	25		4,96	111						550,6		
16	A-IIIIN	16		12	88					1056,0			
17	A-IIIIN	16		4,6	76					349,6			
18	A-IIIIN	16		7,6	218					1656,8			
19	A-IIIIN	16		9,3	130					1209,0			
19A	A-IIIIN	16		10	30					300,0			
20	A-IIIIN	16		6,8	55					374,0			
21	A-IIIIN	16		5,8	12					69,6			
22	A-IIIIN	16		2,5	10					25,0			
23	A-IIIIN	16		8,5	160					1360,0			
24	A-IIIIN	16		3	64					192,0			
25	A-IIIIN	16		3,6	129					464,4			
26	A-IIIIN	10		2,49	640			1593,6					
zbrojenie górne													
18	A-IIIIN	16		7,6	150					1140,0			
30	A-IIIIN	16		8,6	146					1255,6			
31	A-IIIIN	16		8,3	75					622,5			

OBIEKT : Budynek mieszkalny w Będzinie				WYKAZ STALI 2									
ELEMENT : B - Płyta fundamentowa - segment 2				NR RYSUNKU : K2-K4 STRONA 2 z 2									
WYKONAŁ:				DATA:									
Nr	Stal	φ	KSZTAŁT (mm)	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0 St0S		A-IIIIN RB500W					
						6	8	8	10	12	16	20	25
32	A-IIIIN	16		6,6	100						660,0		
33	A-IIIIN	16		7	160						1120,0		
34	A-IIIIN	16		4,3	85						365,5		
21	A-IIIIN	16		5,8	20						116,0		
21A	A-IIIIN	16		6,6	30						198,0		
35	A-IIIIN	16		6,3	120						756,0		
36	A-IIIIN	16		5,5	162						891,0		
37	A-IIIIN	16		7,3	40						292,0		
			łączniki do ścian i słupów oraz zbrojenie dodatkowe										
40	A-IIIIN	12		2,81	325					913,3			
41	A-IIIIN	12		2,76	200					552,0			
42	A-IIIIN	12		2,71	38					103,0			
50	A-IIIIN	12		3,79	24					91,0			
51	A-IIIIN	12		4,73	18					85,1			
52	A-IIIIN	12		2,39	24					57,4			
53	A-IIIIN	12		3,39	18					61,0			
54	A-IIIIN	12		2,8	44					123,2			
60	A-IIIIN	20		2,4	82							196,8	
61	A-IIIIN	20		2,4	24							57,6	
62	A-IIIIN	16		6,3	2						12,6		
80 mb	A-IIIIN	12		500	1					500,0			
100	A-IIIIN	10		1,67	1370				2287,9				

poz 100- 3szt/m2

mb	1484	0	0	3882	2706	14486	1539	551
kg	0,222	0,394	0,394	0,616	0,887	1,578	2,465	3,850
kg	329	0	0	2392	2401	22852	3794	2120
kg	329		33558					
kg	33887							

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)