


















| | | | | | | | | | | | | | | | |
|--|--------|----|-------------------|-------------------------|------------------|--------------------|---|---------------|-------|--------|----|----|---|--|-------|
| OBIEKT : Budynek mieszkalny C Rudzie Śląskiej | | | | w | WYKAZ STALI 20 | | | | | | | | | | |
| ELEMENT : ŚCIANY 2 KONDYGNACJI | | | | NR RYSUNKU : K20, 21 | | | | | | | | | | | |
| WYKONAŁ: | | | | DATA: | | | | | | | | | | | |
| Nr | Stal | φ | KSZTAŁT [mm] | DŁUG. PRĘTA [m] | ILOSC [szt] | DŁUGOSC OGOLNA [m] | | | | | | | | | |
| | | | | | | A-0 St0S | | A-IIIN RB500W | | | | | | | |
| | | | | | | 6 | 8 | 8 | 10 | 12 | 16 | 20 | 6 | | |
| ZLICZYĆ wykaz dla 1-nej kondygn. | | | | | | | | | | | | | | | |
| 1 | A-IIIN | 12 | | 3,6 | 1212 | | | | | 4363,2 | | | | | |
| 2 | A-IIIN | 10 | | 3,5 | 160 | | | | 560,0 | | | | | | |
| łącznik z wieńca do siatek | | | | | | | | | | | | | | | |
| 3 | A-IIIN | 8 | 110 | 1,41 | 360 | | | 507,6 | | | | | | | |
| 4 | A-IIIN | 8 | 170 | 1,47 | 670 | | | 984,9 | | | | | | | |
| 5 | A-0 | 6 | | 0,21 | 000 | 126,0 | | | | | | | | | |
| 6 | A-0 | 6 | | 0,27 | 000 | 270,0 | | | | | | | | | |
| łączniki w narożach | | | | | | | | | | | | | | | |
| 8 | A-IIIN | 8 | 110 | 0,91 | 150 | | | 136,5 | | | | | | | |
| 9 | A-IIIN | 8 | 150 | 1,15 | 325 | | | 373,75 | | | | | | | |
| łączniki przy otworach | | | | | | | | | | | | | | | |
| 10 | A-IIIN | 8 | 110 | 0,61 | 635 | | | 387,4 | | | | | | | |
| 11 | A-IIIN | 8 | 170 | 0,67 | 153 | | | 102,5 | | | | | | | |
| strzemiona filarów | | | | | | | | | | | | | | | |
| 13 | A-IIIN | 6 | 110 | 1,42 | 52 | | | | | | | | | | 73,8 |
| 14 | A-IIIN | 6 | 110 | 1,52 | 26 | | | | | | | | | | 39,5 |
| 15 | A-IIIN | 6 | 110 | 1,76 | 130 | | | | | | | | | | 228,8 |
| 16 | A-IIIN | 6 | 110 | 1,92 | 26 | | | | | | | | | | 49,9 |
| 17 | A-IIIN | 6 | 170 | 1,04 | 24 | | | | | | | | | | 25,0 |
| 18 | A-IIIN | 6 | 170 | 0,98 | 24 | | | | | | | | | | 23,5 |
| 19 | A-IIIN | 6 | 170 | 1,96 | 12 | | | | | | | | | | 23,5 |
| 19a | A-IIIN | 6 | 170 | 2,04 | 12 | | | | | | | | | | 24,5 |
| 20 | A-IIIN | 6 | 110 | 1,26 | 12 | | | | | | | | | | 15,1 |
| 21 | A-IIIN | 6 | 110 | 0,74 | 12 | | | | | | | | | | 8,9 |



| | | | | | | | | | | | | | | |
|--|--------|----|---|-------------------------|----------------------|--------------------|---|---------------|------|--------|--------------|----|---|------|
| OBIEKT : Budynek mieszkalny C Rudzie Śląskiej | | | | W | WYKAZ STALI 20 | | | | | | | | | |
| ELEMENT : ŚCIANY 2 KONDYGNACJI | | | | | NR RYSUNKU : K20, 21 | | | | | | STRONA 2 z 3 | | | |
| WYKONAŁ: | | | | DATA: | | | | | | | | | | |
| Nr | Stal | φ | KSZTAŁT [mm] | DŁUG. PRĘTA [m] | ILOSC [szt] | DŁUGOSC OGOLNA [m] | | | | | | | | |
| | | | | | | A-0 St0S | | A-IIIN RB500W | | | | | | |
| | | | | | | 6 | 8 | 8 | 10 | 12 | 16 | 20 | 6 | |
| | | | No1 szt.8 | | | | | | | | | | | |
| 31 | A-IIIN | 6 |  | 1,08 | 88 | | | | | | | | | 95,0 |
| 32 | A-IIIN | 12 |  | 4 | 16 | | | | | 64,0 | | | | |
| 33 | A-IIIN | 8 |  | 3 | 16 | | | 48,0 | | | | | | |
| | | | No1A szt.8 | | | | | | | | | | | |
| 31 | A-IIIN | 6 |  | 1,08 | 88 | | | | | | | | | 95,0 |
| 32 | A-IIIN | 12 |  | 40 | 32 | | | | | 1280,0 | | | | |
| 33 | A-IIIN | 8 |  | 3 | 80 | | | 240,0 | | | | | | |
| 34 | A-IIIN | 8 |  | 0,9 | 176 | | | 158,4 | | | | | | |
| | | | No2 szt.4 | | | | | | | | | | | |
| 31 | A-IIIN | 6 |  | 1,08 | 36 | | | | | | | | | 38,9 |
| 35 | A-IIIN | 10 |  | 3 | 16 | | | | 48,0 | | | | | |
| 36 | A-IIIN | 8 |  | 2,5 | 40 | | | 100,0 | | | | | | |
| 34 | A-IIIN | 8 |  | 0,9 | 64 | | | 57,6 | | | | | | |
| | | | No3 szt.7 | | | | | | | | | | | |
| 31 | A-IIIN | 6 |  | 1,08 | 42 | | | | | | | | | 45,4 |
| 37 | A-IIIN | 10 |  | 2,5 | 28 | | | | 70,0 | | | | | |
| 38 | A-IIIN | 8 |  | 2 | 70 | | | 140,0 | | | | | | |
| 34 | A-IIIN | 8 |  | 0,9 | 84 | | | 75,6 | | | | | | |



| | | | | | | | | | | | | | |
|--|--------|----|--------------------------|-----------------------|----------------|--------------------|---|------|------|---------------|----|----|------|
| OBIEKT : Budynek mieszkalny C Rudzie Śląskiej | | | | W WYKAZ STALI 20 | | | | | | | | | |
| ELEMENT : ŚCIANY 2 KONDYGNACJI | | | | NR RYSUNKU : K20, 21 | | | | | | | | | |
| WYKONAŁ: | | | | DATA: | | | | | | | | | |
| Nr | Stal | φ | KSZTAŁT (mm) | DŁUG. PRĘTA [m] | ILOSC [szt] | DŁUGOSC OGOLNA [m] | | | | | | | |
| | | | | | | A-0 St0S | | | | A-IIIN RB500W | | | |
| | | | | | | 6 | 8 | 8 | 10 | 12 | 16 | 20 | 6 |
| | | | No6 szt.1 | | | | | | | | | | |
| 32 | A-IIIN | 10 | 3600 | 3,6 | 4 | | | | 14,4 | | | | |
| 33 | A-IIIN | 8 | 3000 | 3 | 10 | | | 30,0 | | | | | |
| 39 | A-IIIN | 8 | 1400 | 1,4 | 20 | | | 28,0 | | | | | |
| | | | Nd1 szt.7 Nd2 szt.1 | | | | | | | | | | |
| 41 | A-IIIN | 6 | 710 50 50 170 710 170 | 1,86 | 42 | | | | | | | | 78,1 |
| 42 | A-IIIN | 10 | 2600 | 2,6 | 10 | | | | 26,0 | | | | |
| 43 | A-IIIN | 8 | 2000 | 2 | 28 | | | 56,0 | | | | | |
| | | | Nd3 szt.1 | | | | | | | | | | |
| 48 | A-IIIN | 6 | 590 50 50 110 590 110 | 1,5 | 8 | | | | | | | | 12,0 |
| 46 | A-IIIN | 10 | 1850 | 1,85 | 2 | | | | 3,7 | | | | |
| 47 | A-IIIN | 8 | 1850 | 1,85 | 4 | | | 7,4 | | | | | |
| | | | | | | | | | | | | | |

siatki R378 (2,15x6,0m) szt.80

| | | | | | | | | |
|----|-------|-------|-------|-------|-------|-------|-------|-------|
| mb | 000 | 0 | 3440 | 722 | 5707 | 0 | 0 | 877 |
| kg | 0,222 | 0,394 | 0,394 | 0,616 | 0,887 | 1,578 | 2,465 | 0,222 |
| kg | 00 | 0 | 1357 | 445 | 5064 | 0 | 0 | 195 |
| 00 | | 7061 | | | | | | |
| kg | | 7061 | | | | | | |

UWAGA

x 1 kondygnacje

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)