






























OBIEKT :				Budynek mieszkalny E w Rudzie Śląskiej		WYKAZ STALI									
ELEMENT :				Strop nad 1 2 3 4 piętrzem budynek E segment E1 - wieńce zbrojenie górne		NR RYSUNKU :				K22		STRONA		1 z 2	
WYKONAŁ:															
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]									
						A-0		A-IIIIN							
						6	8	8	10	12	16	20	6		
1	A-IIIIN	12		12	8					96,0					
2	A-IIIIN	12		12	12					144,0					
3	A-IIIIN	12		4,7	4					18,8					
4	A-IIIIN	12		7,9	0					0,0					
5	A-IIIIN	16		12	20						240,0				
6	A-IIIIN	16		12	8					96,0					
7	A-IIIIN	16		4,7	4					18,8					
8	A-IIIIN	16		7,9	16					126,4					
9	A-0	6		0,64	290	185,6									
10	A-0	6		0,74	570	421,8									
12	A-IIIIN	16		9,3	12						111,6				
13	A-IIIIN	16		11,04	4						44,2				
14	A-IIIIN	16		7,4	4						29,6				
15	A-IIIIN	16		6,1	4						24,4				
16	A-IIIIN	12		0	1					0,0					
17	A-IIIIN	12		8,8	4					35,2					
18	A-IIIIN	12		11,06	4					44,2					
19	A-IIIIN	16		7,7	8						61,6				
20	A-IIIIN	16		7,1	4						28,4				
21	A-IIIIN	16		4,7	4						18,8				
30	A-IIIIN	16		4,8	300						1440,0				
31	A-IIIIN	16		4,1	85						348,5				
32	A-IIIIN	12		3,5	190					665,0					
33	A-IIIIN	16		6,1	45						274,5				
34	A-IIIIN	12		7	70					490,0					
35	A-IIIIN	12		5,4	48					259,2					
36	A-IIIIN	10		2	40				80,0						
37	A-IIIIN	12		8	24					192,0					



OBIEKT :				Budynek mieszkalny E w Rudzie Śląskiej		WYKAZ STALI									
ELEMENT :				Strop nad 1 2 3 4 piętrem budynek E segment E1 - wieńce zbrojenie górne		NR RYSUNKU :				K22		STRONA 2 z 2			
WYKONAŁ:															
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]									
						A-0		A-IIIIN							
						6	8	8	10	12	16	20	6		
38	A-IIIIN	12		4,92	12					59,0					
39 mb	A-IIIIN	6		1200	1								1200,0		
40	A-IIIIN	8		1,32	410			541,2							
41	A-IIIIN	12		2,18	205					446,9					
42	A-IIIIN	16		5	4						20,0				
			Bs1 szt.1												
45	A-IIIIN	20		2,28	2							4,6			
46	A-IIIIN	12		2,8	2					5,6					
46a	A-IIIIN	10													
47	A-IIIIN	8		1,12	15			16,8							
			Bs2 szt.1												
48	A-IIIIN	16													
49	A-IIIIN	12		4,2	2					8,4					
50	A-IIIIN	8		0,94	24			22,6							
			Bsp szt.1												
51	A-IIIIN	12													
52	A-IIIIN	12													
53	A-IIIIN	10													
54	A-IIIIN	8		0,84	10			8,4							
55	A-IIIIN	20													
			belki dla 2, 3, 4 kondygn. B1 szt.2												
70	A-IIIIN	16		3,5	6						21,0				
71	A-IIIIN	10													
72	A-IIIIN	10		1,14	32				36,5						
			B2 szt.3												
73	A-IIIIN	16													
74	A-IIIIN	10													
75	A-IIIIN	10		1,64	27				44,3						

UWAGA
wykaz dotyczy tylko 1 stropu

mb	607	0	48	81	209	725	5	1200
kg	0,222	0,394	0,394	0,616	0,887	1,578	2,465	0,222
kg	135	0	19	50	185	1291	12	266
kg	135		1557					
kg	1692							

UWAGA
WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)