






























OBJEKT :				Budynek mieszkalny D w Rudzie Śląskiej		WYKAZ STALI											
ELEMENT :				Strop nad 3 piętrem budynek D segment D1 wieńce zbrojenie górne		NR RYSUNKU :				K22		STRONA				1 z 2	
WYKONAŁ:																	
Nr	Stal	φ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]											
						A-0		A-IIIIN									
						6	8	8	10	12	16	20	6				
1	A-IIIIN	12		12	12						144,0						
2	A-IIIIN	12		12	4						48,0						
3	A-IIIIN	12		5,2	4						20,8						
4	A-IIIIN	12		11,5	4						46,0						
5	A-IIIIN	12		7,9	4						31,6						
6	A-IIIIN	16		6,7	4						26,8						
8	A-IIIIN	16		12	12						144,0						
9	A-0	6		0,64	250	160,0											
10	A-0	6		0,74	460	340,4											
11	A-IIIIN	16		7,9	8						63,2						
12	A-IIIIN	16		9,33	20						186,6						
14 mb	A-IIIIN	12		25	1						25,0						
15	A-IIIIN	16		9,4	4						37,6						
16	A-IIIIN	16		7,3	4						29,2						
17	A-IIIIN	16		4,85	4						19,4						
18	A-IIIIN	16		5,85	4						23,4						
19	A-IIIIN	16		8	4						32,0						
30	A-IIIIN	16		4,8	295						1416,0						
31	A-IIIIN	12		4,1	75						307,5						
32	A-IIIIN	12		6,8	90						612,0						
33	A-IIIIN	16		6,1	40						244,0						
34	A-IIIIN	12		3,8	90						342,0						
36	A-IIIIN	10		2	8					16,0							
39 mb	A-IIIIN	6		1000	1										1000,0		
40	A-IIIIN	8		1,32	330				435,6								
41	A-IIIIN	12		2,18	160						348,8						



OBIEKT : Budynek mieszkalny D w Rudzie Śląskiej				WYKAZ STALI									
ELEMENT : Strop nad 3 piętrem budynek D segment D1 wieńce zbrojenie górne				NR RYSUNKU : K22 STRONA 2 z 2									
WYKONAŁ:													
Nr	Stal	φ	KSZTAŁT (mm)	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0				A-IIIIN			
						6	8	8	10	12	16	20	6
			Bs1 szt.1										
45	A-IIIIN	20	200 3200	3,4	2							6,8	
46	A-IIIIN	16	200 4000	4,2	3						12,6		
46a	A-IIIIN	10	4000	4	2				8,0				
47	A-IIIIN	8	160 350 50,50 160 350	1,12	20			22,4					
			Bs2 szt.1										
48	A-IIIIN	16	3100	3,1	3						9,3		
49	A-IIIIN	12	4200	4,2	2					8,4			
50	A-IIIIN	8	160 260 50,50 160 260	0,94	24			22,6					
			belki dla 2, 3, 4 kondygn. B1 szt.3										
70	A-IIIIN	20	3500	3,5	9							31,5	
71	A-IIIIN	10	3000	3	12				36,0				
72	A-IIIIN	10	170 350 50,50 170 350	1,14	48				54,7				
			B2 szt.1										
73	A-IIIIN	20	3200	3,2	2							6,4	
74	A-IIIIN	10	3000	3	6				18,0				
75	A-IIIIN	10	170 600 50,50 170 600	1,64	9				14,8				

UWAGA
wykaz dotyczy tylko 1 stropu

mb	500	0	45,4	131	251	584	45	
kg	0,222	0,394	0,394	0,616	0,887	1,578	2,465	
kg	111	0	18	81	223	922	111	
kg	111		1466					

UWAGA
WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)