



|   |        |    |                   |                         |                  |                    |   |       |     |               |    |    |      |
|---|--------|----|-------------------|-------------------------|------------------|--------------------|---|-------|-----|---------------|----|----|------|
| OBIEKT : Budynek mieszkalny E<br>w Rudzie Śląskiej    |        |    |                   | WYKAZ STALI             |                  |                    |   |       |     |               |    |    |      |
| ELEMENT : ŚCIANY 2,3,4 PIĘTRA budynek E<br>segment E1 |        |    |                   | NR RYSUNKU : K20, 21    |                  |                    |   |       |     |               |    |    |      |
| WYKONAŁ:  |        |    |                   | DATA:                   |                  |                    |   |       |     |               |    |    |      |
| Nr  | Stal   | φ  | KSZTAŁT<br>( mm ) | DŁUG.<br>PRĘTA<br>[ m ] | ILOSC<br>[ szt ] | DŁUGOSC OGOLNA [m] |   |       |     |               |    |    |      |
|   |        |    |                   |                         |                  | A-0 St0S           |   |       |     | A-IIIN RB500W |    |    |      |
|   |        |    |                   |                         |                  | 6                  | 8 | 8     | 10  | 12            | 16 | 20 | 6    |
| 1   | A-IIIN | 12 |                   | 3,6                     | 1380             |                    |   |       |     | 4968,0        |    |    |      |
| 2   | A-IIIN | 10 |                   | 3,5                     | 40               |                    |   |       | 140 |               |    |    |      |
| łącznik z wieńca do ścian                             |        |    |                   |                         |                  |                    |   |       |     |               |    |    |      |
| 3   | A-IIIN | 8  |                   | 1,41                    | 290              |                    |   | 408,9 |     |               |    |    |      |
| 4   | A-IIIN | 8  |                   | 1,47                    | 330              |                    |   | 485,1 |     |               |    |    |      |
| 5   | A-0    | 6  |                   |                         |                  |                    |   |       |     |               |    |    |      |
| 6   | A-0    | 6  |                   |                         |                  |                    |   |       |     |               |    |    |      |
| łączniki w narożach                                   |        |    |                   |                         |                  |                    |   |       |     |               |    |    |      |
| 8   | A-IIIN | 8  |                   | 0,91                    | 132              |                    |   | 120,1 |     |               |    |    |      |
| 9   | A-IIIN | 8  |                   | 1,15                    | 430              |                    |   | 494,5 |     |               |    |    |      |
| łączniki przy otworach                                |        |    |                   |                         |                  |                    |   |       |     |               |    |    |      |
| 10  | A-IIIN | 8  |                   | 0,61                    | 290              |                    |   | 176,9 |     |               |    |    |      |
| 11  | A-IIIN | 8  |                   | 0,67                    | 240              |                    |   | 160,8 |     |               |    |    |      |
| strzemiona filarów                                    |        |    |                   |                         |                  |                    |   |       |     |               |    |    |      |
| 13  | A-IIIN | 6  |                   | 1,42                    | 12               |                    |   |       |     |               |    |    | 17,0 |
| 14  | A-IIIN | 6  |                   | 1,52                    | 48               |                    |   |       |     |               |    |    | 73,0 |
|   |        |    |                   |                         |                  |                    |   |       |     |               |    |    |      |
| 16  | A-IIIN | 6  |                   | 1,92                    | 12               |                    |   |       |     |               |    |    | 23,0 |
|   |        |    |                   |                         |                  |                    |   |       |     |               |    |    |      |
|   |        |    |                   |                         |                  |                    |   |       |     |               |    |    |      |
| 21  | A-IIIN | 6  |                   | 0,74                    | 11               |                    |   |       |     |               |    |    | 8,1  |

[illegible]



|  |        |    |                             |                       |                |                    |   |      |     |               |    |    |       |
|--|--------|----|-----------------------------|-----------------------|----------------|--------------------|---|------|-----|---------------|----|----|-------|
| OBIEKT : Budynek mieszkalny E w Rudzie Śląskiej    |        |    |                             | WYKAZ STALI           |                |                    |   |      |     |               |    |    |       |
| ELEMENT : ŚCIANY 2,3,4 PIĘTRA budynek E segment E1 |        |    |                             | NR RYSUNKU : K20, 21  |                |                    |   |      |     |               |    |    |       |
| WYKONAŁ:   |        |    |                             | DATA:                 |                |                    |   |      |     |               |    |    |       |
| Nr   | Stal   | φ  | KSZTAŁT<br>(mm)             | DŁUG.<br>PRĘTA<br>[m] | ILOSC<br>[szt] | DŁUGOSC OGOLNA [m] |   |      |     |               |    |    |       |
|  |        |    |                             |                       |                | A-0 St0S           |   |      |     | A-IIIN RB500W |    |    |       |
|  |        |    |                             |                       |                | 6                  | 8 | 8    | 10  | 12            | 16 | 20 | 6     |
|  |        |    | No6 szt.1                   |                       |                |                    |   |      |     |               |    |    |       |
| 32   | A-IIIN | 12 | 4500                        | 4,5                   | 2              |                    |   |      |     | 9,0           |    |    |       |
| 33   | A-IIIN | 8  | 4500                        | 4,5                   | 18             |                    |   | 81,0 |     |               |    |    |       |
| 39   | A-IIIN | 8  | 2400                        | 2,4                   | 20             |                    |   | 48,0 |     |               |    |    |       |
|  |        |    | Nw szt.1                    |                       |                |                    |   |      |     |               |    |    |       |
| 48   | A-IIIN | 6  | 590 50 50<br>110 110<br>590 | 1,5                   | 8              |                    |   |      |     |               |    |    | 12,0  |
| 46   | A-IIIN | 10 |                             |                       |                |                    |   |      |     |               |    |    |       |
| 47   | A-IIIN | 8  |                             |                       |                |                    |   |      |     |               |    |    |       |
|  |        |    | Np3 szt.1                   |                       |                |                    |   |      |     |               |    |    |       |
| 49   | A-IIIN | 6  | 610 50 50<br>170 170<br>610 | 1,66                  | 9              |                    |   |      |     |               |    |    | 14,9  |
| 50   | A-IIIN | 10 | 3200                        | 3,2                   | 3              |                    |   |      | 9,6 |               |    |    |       |
| 51   | A-IIIN | 8  | 3000                        | 3                     | 4              |                    |   | 12,0 |     |               |    |    |       |
|  |        |    | Nd1 szt.8 Nd2 szt.2         |                       |                |                    |   |      |     |               |    |    |       |
| 41   | A-IIIN | 6  | 900<br>170 170<br>900       | 1,97                  | 60             |                    |   |      |     |               |    |    | 118,2 |
| 42   | A-IIIN | 10 |                             |                       |                |                    |   |      |     |               |    |    |       |
| 43   | A-IIIN | 8  |                             |                       |                |                    |   |      |     |               |    |    |       |
|  |        |    |                             |                       |                |                    |   |      |     |               |    |    |       |

siatki R378 (2,15x6,0m) szt.112

|    |       |       |       |       |       |       |       |       |
|----|-------|-------|-------|-------|-------|-------|-------|-------|
| mb | 000   | 0     | 2556  | 222,0 | 5193  | 0     | 0     | 583   |
| kg | 0,222 | 0,394 | 0,394 | 0,616 | 0,887 | 1,578 | 2,465 | 0,222 |
| kg | 00    | 0     | 1007  | 137   | 4608  | 0     | 0     | 129   |
| kg | 00    |       | 5881  |       |       |       |       |       |

UWAGA

x 1

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH ( metoda A wg PN-EN ISO 3766:2005)