



OBIEKT :

Budynek - Żory ul. Prawnicza

ELEMENT :




















Stropodach budynek D segment D2
wierce zbrojenie górne

WYKONAŁ:

WYKAZ STALI

NR RYSUNKU :K6-K8

STRONA1 z 2

Nr	Stal	ϕ	KSZTAŁT [mm]	DŁUG. PRĘTA [m]	ILOSC [szt]	DŁUGOSC OGOLNA [m]							
						A-0		A-IIIIN					
						6	8	8	10	12	16	20	25
1	A-IIIIN	12	500 	12	4					48,0			
2	A-IIIIN	12		12	4					48,0			
3	A-IIIIN	12	500 	5,2	4					20,8			
5	A-IIIIN	12	500 	7,9	4					31,6			
8	A-IIIIN	16	500 	12	20						240,0		
9	A-0	6	170 	0,64	165	105,6							
10	A-0	6	170 	0,74	390	288,6							
11	A-IIIIN	16	500 	7,9	20						158,0		
13	A-IIIIN	12	500 	8,5	4					34,0			
14 mb	A-IIIIN	12		25	1					25,0			
20	A-IIIIN	12	500 	11,1	4					44,4			
21	A-IIIIN	16	500 	7,85	4						31,4		
22	A-IIIIN	16	500 	7,55	8						60,4		
23	A-IIIIN	16	500 	6,8	4						27,2		
24	A-IIIIN	16	500 	5,85	4						23,4		
30	A-IIIIN	16		4,8	120						576,0		
31	A-IIIIN	12		4,1	230					943,0			
35	A-IIIIN	12		7	80					560,0			
37	A-IIIIN	10		3,2	50				160,0				
39 mb	A-IIIIN	6											
40	A-IIIIN	8											
41	A-IIIIN	12											
			belki dla 2, 3, 4 kondygn. B1 szt.2										
70	A-IIIIN	20											
71	A-IIIIN	10											
72	A-IIIIN	10											

[illegible]

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)