
























| | | | | | | | | | | | | | | |
|---------------------------------------|---------|----|--|-------------------------|-----------------------|--------------------|---|----------------|-------|--------|----|----|-------|--|
| OBIEKT : Budynek mieszkalny C | | | | w | WYKAZ STALI 24 | | | | | | | | | |
| ELEMENT : ŚCIANY 5 KONDYGNACJI | | | | | NR RYSUNKU : K24, 25 | | | | | | | | | |
| WYKONAŁ: | | | | DATA: | | | | | | | | | | |
| Nr | Stal | φ | KSZTAŁT [mm] | DŁUG. PRĘTA [m] | ILOSC [szt] | DŁUGOSC OGOLNA [m] | | | | | | | | |
| | | | | | | A-0 St0S | | A-IIIIN RB500W | | | | | | |
| | | | | | | 6 | 8 | 8 | 10 | 12 | 16 | 20 | 6 | |
| | | | | | | | | | | | | | | |
| 1 | A-IIIIN | 12 | <div><div>3600</div></div> | 3,6 | 38 | | | | | 136,8 | | | | |
| 1a | A-IIIIN | 12 | <div><div>2940</div></div> | 2,94 | 1212 | | | | | 3563,3 | | | | |
| 2a | A-IIIIN | 10 | <div><div>3600</div></div> | 3,6 | 160 | | | | 576,0 | | | | | |
| | | | łącznik z wieńca do siatek | | | | | | | | | | | |
| 7 | A-IIIIN | 8 | <div><div>110</div><div><div>850</div></div></div> | 1,81 | 330 | | | 597,3 | | | | | | |
| 7b | A-IIIIN | 8 | <div><div>110</div><div><div>850</div><div>1100</div></div></div> | 2,31 | 42 | | | 97,0 | | | | | | |
| 5 | A-0 | 6 | <div><div>1100</div></div> | | | | | | | | | | | |
| 6 | A-0 | 6 | | | | | | | | | | | | |
| | | | łączniki w narożach | | | | | | | | | | | |
| 8 | A-IIIIN | 8 | <div><div>110</div><div><div>400</div></div></div> | 0,91 | 156 | | | 142,0 | | | | | | |
| 9 | A-IIIIN | 8 | <div><div>170</div><div><div>400</div><div>500</div></div></div> | 1,17 | 325 | | | 380,3 | | | | | | |
| | | | łączniki przy otworach | | | | | | | | | | | |
| 10 | A-IIIIN | 8 | <div><div>110</div><div><div>250</div></div></div> | 0,61 | 600 | | | 366,0 | | | | | | |
| 11 | A-IIIIN | 8 | <div><div>170</div><div><div>250</div></div></div> | 0,67 | 180 | | | 120,6 | | | | | | |
| | | | strzemiona filarów | | | | | | | | | | | |
| 13 | A-IIIIN | 6 | <div><div>110</div><div><div>550</div><div>50,50</div></div></div> | 1,42 | 52 | | | | | | | | 73,8 | |
| 14 | A-IIIIN | 6 | <div><div>110</div><div><div>550</div><div>600</div><div>50,50</div></div></div> | 1,52 | 26 | | | | | | | | 39,5 | |
| 15 | A-IIIIN | 6 | <div><div>110</div><div><div>600</div><div>720</div><div>50,50</div></div></div> | 1,76 | 130 | | | | | | | | 228,8 | |
| 16 | A-IIIIN | 6 | <div><div>110</div><div><div>720</div><div>800</div><div>50,50</div></div></div> | 1,92 | 26 | | | | | | | | 49,9 | |
| 17 | A-IIIIN | 6 | <div><div>170</div><div><div>300</div><div>50,50</div></div></div> | 1,04 | 24 | | | | | | | | 25,0 | |
| 18 | A-IIIIN | 6 | <div><div>170</div><div><div>300</div><div>270</div><div>50,50</div></div></div> | 0,98 | 24 | | | | | | | | 23,5 | |
| 19 | A-IIIIN | 6 | <div><div>170</div><div><div>270</div><div>760</div><div>50,50</div></div></div> | 1,96 | 12 | | | | | | | | 23,5 | |
| 19a | A-IIIIN | 6 | <div><div>170</div><div><div>760</div><div>800</div><div>50,50</div></div></div> | 2,04 | 12 | | | | | | | | 24,5 | |
| 20 | A-IIIIN | 6 | <div><div>110</div><div><div>800</div><div>470</div><div>50,50</div></div></div> | 1,26 | 12 | | | | | | | | 15,1 | |
| 21 | A-IIIIN | 6 | <div><div>110</div><div><div>470</div><div>210</div><div>50,50</div></div></div> | 0,74 | 12 | | | | | | | | 8,9 | |



| | | | | | | | | | | | | | | |
|--|--------|----|---|-------------------------|----------------------|--------------------|---|---------------|-------|----|----|----|---|-------|
| OBIEKT : Budynek mieszkalny C Rudzie Śląskiej | | | | w | WYKAZ STALI 24 | | | | | | | | | |
| ELEMENT : ŚCIANY 5 KONDYGNACJI | | | | | NR RYSUNKU : K24, 25 | | | | | | | | | |
| WYKONAŁ: | | | | STRONA 2 z 3 | | | | | | | | | | |
| | | | | DATA: | | | | | | | | | | |
| Nr | Stal | φ | KSZTAŁT [mm] | DŁUG. PRĘTA [m] | ILOSC [szt] | DŁUGOSC OGOLNA [m] | | | | | | | | |
| | | | | | | A-0 St0S | | A-IIIN RB500W | | | | | | |
| | | | | | | 6 | 8 | 8 | 10 | 12 | 16 | 20 | 6 | |
| | | | No1 szt.8 | | | | | | | | | | | |
| 31 | A-IIIN | 6 | 110  | 1,31 | 88 | | | | | | | | | 115,3 |
| 32 | A-IIIN | 10 |  | 3,6 | 16 | | | | 57,6 | | | | | |
| 33 | A-IIIN | 8 |  | 3 | 16 | | | 48,0 | | | | | | |
| | | | No1A szt.8 | | | | | | | | | | | |
| 31 | A-IIIN | 6 | 110  | 1,31 | 88 | | | | | | | | | 115,3 |
| 32 | A-IIIN | 10 |  | 3,6 | 32 | | | | 115,2 | | | | | |
| 33 | A-IIIN | 8 |  | 3 | 80 | | | 240,0 | | | | | | |
| 34 | A-IIIN | 8 | | | | | | | | | | | | |
| | | | No2 szt.4 | | | | | | | | | | | |
| 31 | A-IIIN | 6 | 110  | 1,31 | 32 | | | | | | | | | 41,9 |
| 35 | A-IIIN | 10 |  | 3 | 16 | | | | 48,0 | | | | | |
| 36 | A-IIIN | 8 |  | 2,5 | 40 | | | 100,0 | | | | | | |
| 34 | A-IIIN | 8 | | | | | | | | | | | | |
| | | | No3 szt.7 | | | | | | | | | | | |
| 31 | A-IIIN | 6 | 110  | 1,31 | 42 | | | | | | | | | 55 |
| 37 | A-IIIN | 10 |  | 2,5 | 28 | | | | 70,0 | | | | | |
| 38 | A-IIIN | 8 |  | 2 | 70 | | | 140,0 | | | | | | |
| 34 | A-IIIN | 8 | | | | | | | | | | | | |
| | | | No6a szt.1 | | | | | | | | | | | |
| 32 | A-IIIN | 10 |  | 3,6 | 2 | | | | 7,2 | | | | | |
| 33 | A-IIIN | 8 |  | 3 | 10 | | | 30,0 | | | | | | |
| 39a | A-IIIN | 8 |  | 1,94 | 20 | | | 38,8 | | | | | | |



| | | | | | | | | | | | | | |
|--|--------|----|---|-------------------------|------------------|--------------------|---|---------------|------|----|----|----|------|
| OBIEKT : Budynek mieszkalny C Rudzie Śląskiej | | | | w WYKAZ STALI 24 | | | | | | | | | |
| ELEMENT : ŚCIANY 5 KONDYGNACJI | | | | NR RYSUNKU : K24, 25 | | | | | | | | | |
| WYKONAŁ: | | | | DATA: | | | | | | | | | |
| Nr | Stal | φ | KSZTAŁT (mm) | DŁUG. PRĘTA [m] | ILOSC [szt] | DŁUGOSC OGOLNA [m] | | | | | | | |
| | | | | | | A-0 St0S | | A-IIIN RB500W | | | | | |
| | | | | | | 6 | 8 | 8 | 10 | 12 | 16 | 20 | 6 |
| | | | Nd1 szt.7 Nd2 szt.1 | | | | | | | | | | |
| 41 | A-IIIN | 6 | 170  170 | 1,86 | 42 | | | | | | | | 78,1 |
| 42 | A-IIIN | 10 |  2600 | 2,6 | 10 | | | | 26,0 | | | | |
| 43 | A-IIIN | 8 |  2000 | 2 | 28 | | | 56,0 | | | | | |
| | | | Nd3 szt.1 | | | | | | | | | | |
| 48 | A-IIIN | 6 | 110  900 | 1,91 | 8 | | | | | | | | 15,3 |
| 46 | A-IIIN | 10 |  1850 | 1,85 | 2 | | | | 3,7 | | | | |
| 47 | A-IIIN | 8 |  1850 | 1,85 | 4 | | | 7,4 | | | | | |
| | | | | | | | | | | | | | |

siatki R378 (2,15x6,0m) szt.88

| | | | | | | | | |
|-----------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| mb kg kg kg kg | 000 | 0 | 2363 | 904 | 3700 | 0 | 0 | 933 |
| | 0,222 | 0,394 | 0,394 | 0,616 | 0,887 | 1,578 | 2,465 | 0,222 |
| | 00 | 0 | 931 | 557 | 3283 | 0 | 0 | 207 |
| | 00 | | 4978 | | | | | |
| 4978 | | | | | | | | |

UWAGA

WYMIAROWANIE ZBROJENIA na PODSTAWIE WYMIARÓW ZEWNĘTRZNYCH (metoda A wg PN-EN ISO 3766:2005)